

# HAF BASKET FAN SERIES

**HORTICULTURE**

## PRODUCT HIGHLIGHTS

### FEATURES:

- Standard OSHA safety guards on intake and exhaust. Open Style guards available upon special order need to be mounted 7' or higher above ground
- Powder coated guards for corrosion-resistance
- Versatile wall and ceiling mount pivots 180° and fan can turn 360°
- Well balanced and strong blade design for years of trouble free service
- Designed for optimum air throw and coverage
- Motors are totally enclosed, high efficiency with sealed ball bearings.
- Variable speed operation with optional speed controls
- Easy to clean with no corners for dirt or disease build-up
- Some assembly required
- 2 year warranty on Motor and 1 year limited warranty on all other parts

### IDEAL APPLICATIONS:

- Greenhouse cooling
- Machine and compressor cooling.
- Insect control
- Air de-stratification
- Create a consistent air temperature in buildings or greenhouses
- Surface drying for wet floors



**Environmental Solutions, LLC.**  
[vesenviro.com](http://vesenviro.com)

8296 Commerce Pkwy,  
 Chippewa Falls, WI 54729 USA  
 Toll Free Tel.: (888) 622-2999  
 Tel.: (715) 720-0800  
[info@vesenviro.com](mailto:info@vesenviro.com)



**Open Guard**



**12"                      20 - 36"**

**Hanging Brackets**



Our HAF Basket Fan series of OSHA compliant and optional Open Style Guard gives you great performance, energy efficiency and an air pattern that is designed for heat de-stratification. The OSHA compliant guard means the fan can be mounted at any height. The totally enclosed motor can be used in harsh agricultural, horticultural and industrial environments. Optional 9' cord (C) for no electrician required installation.

### MOTOR FEATURES:

- Motor is CSA/CSA-US approved
- 50/60 hz
- Rotors have been balanced to reduce noise reduce vibration and prolong life
- Motor enclosures have been machined to <0.5mm to reduce rotor shaft play



- Copper Windings
- Bearing Specifications -40°C to 140°C
- Capacitor rating 450vac, 10,000 hours for extended life
- Silicon steel rotors and stators



**Two year warranty on Motor and 1 year limited warranty on all other parts.**

Part #	Size	HP	Spd	Voltage	Ph	AMP	RPM	HZ	Cord	Wt. lb	Color
HAF18110COG	18"	1/10	VAR	115	1	1.35	1725	60	9'	26	White
HAF20110C	20"	1/10	VAR	115	1	1.35	1725	60	9'	28	White
HAF3012	30"	1/2	VAR	115/230	1	6.35/3.18	850	60	N/A	50.25	Black
HAF3012C	30"	1/2	VAR	115	1	6.35	850	60	9'	50.25	Black

**OG = Open Guard (non-OSHA compliant)**

*Standard finish available in white & black.*