

MOISTURE RESISTANT WALL/CEILING MOUNT

INDUSTRIAL

PRODUCT HIGHLIGHTS

FEATURES:

- High velocity air movement
- Constructed with high-grade steel
- Factory balanced aluminium blades
- Fan head tilt able to 105°
- Powder coated guard, blade, base and pole for corrosion resistance
- 3 speed with pull chain
- Attached adjustable wall mount bracket pivots up to 140°
- Adjustable ceiling or wall mount bracket attached
- 1 year warranty

APPLICATIONS:

- Greenhouse
- Patios (with GFI Cord)
- Moisture applications
- Industrial



OSHA Compliant



Open Guard

Our Moisture Resistant Basket Fan series of OSHA compliant and optional Open Style Guard gives you great performance, energy efficiency and an air pattern that is designed for heat de-stratification. The OSHA compliant guard means the fan can be mounted at any height. The totally enclosed air over motor can be used in harsh horticultural and industrial environments.

ADDITIONAL FEATURES:

- Wall and ceiling mount available in 18"
- High velocity air movement
- Constructed with high-grade steel
- Factory balanced aluminium blades
- UL507 with GFI Cord available on special order only, tested and rated for use with misting and fogging rings for indoor and outdoor use
- Fan head tilt able to 105°
- Guard, blade, and bracket powder coated for corrosion resistance
- 3 speed with pull chain.
- Motor is CSA/CSA-US approved
- Direct drive motor is completely sealed with permanently lubricated ball bearings with thermal overload protection
- Adjustable wall mount bracket pivots up to 140°
- 1 year warranty



Environmental Solutions, LLC.

vesenviro.com

8296 Commerce Pkwy,
Chippewa Falls, WI 54729 USA
Toll Free Tel.: (888) 622-2999
Tel.: (715) 720-0800
info@vesenviro.com

SPECIFICATIONS

Model	Size	Spd	HP	RPM		CFM @ .0 SP		CFM/Watt @ .0 SP		AMPS		Cord
				Hi/Med/Lo	HZ	Hi/Med/Lo	Hi/Med/Lo	Voltage	Hi/Med/Lo			
HVW-18M	18"	3	1/10	1570/1400/1000	60	6357/5086/4068	38/34/31	120	1.45/1.35/1.27	12'		
HVW-18MB	18"	3	1/10	1570/1400/1000	60	6357/5086/4068	38/34/31	120	1.45/1.35/1.27	12'		
HVW-18M-OG	18"	3	1/10	1570/1400/1000	60	6357/5086/4068	38/34/31	120	1.45/1.35/1.27	12'		
HVW-18MB-OG	18"	3	1/10	1570/1400/1000	60	6357/5086/4068	38/34/31	120	1.45/1.35/1.27	12'		

OG = Open Guard (non-OSHA compliant)