

VESCO422 MULTI-STAGE CONTROL

INDUSTRIAL

PRODUCT HIGHLIGHTS

FEATURES:

- Automatic temperature-based control
- Seven configurable operation programs
- Adjustable temperature set-point and differential
- Adjustable high/low temperature alert settings
- Two variable stages
- Three general-purpose relays (heat, cool or disconnect)
- One alarm relay (for external alarm system or siren)
- Four-character LED display and individual stage LEDs
- Fahrenheit and Celsius display
- Minimum and maximum temperature logging
- Error code display for troubleshooting
- Three-second full-power-turn-on to minimize fan ice-up
- Ventilation disable option
- Manual override/test mode
- One temperature probe input
- Power-failure memory protection
- 30-foot temperature probe, extendable to 500 feet
- Overload protection fuses
- Rugged enclosure (corrosion resistant, water resistant and fire retardant)
- CSA approved
- Two-year limited warranty



Input power	120/230 VAC, 50/60 Hz
Variable stages	10 A at 120/230 VAC, general-purpose (resistive) 7 FLA at 120/230 VAC, PSC motor 1/2 HP at 120 VAC, 1 HP at 230 VAC, PSC motor
Variable stage fuses	15 A, 250 VAC ABC-type ceramic
DC signal output (V1, V2)	1 to 10 VDC, 2K Ω load
Relay stages ① (STAGE 3, STAGE 4, STAGE 5)	6 A at 120/230 VAC, general-purpose (resistive) 1/3 HP at 120 VAC, 1/2 HP at 230 VAC 360 W tungsten at 120 VAC
Relay Fuses (F1, F4 and F5)	12 A, 250 VAC ABC-type ceramic
Alarm relay	0.4 A at 125 VAC; 2 A at 30 VDC, resistive load 0.2 A at 125 VAC; 1 A at 30 VDC, inductive load
① You can connect more than one piece of equipment to a relay as long as they are the same type (for example, two fans) and the total current draw does not exceed the stage's limit.	

VES Environmental Solutions, LLC is North America's most innovative ventilation and environmental control company. Our new VESCO422 control is designed to run multiple fans which are controlled by VFD's (Variable Frequency Drive). This control can run two stages of 0-10V DC signals for the VFD's on our 72" and 50" ECVC Fans and AFR72" and AFR50" variable exhaust fans. The VESCO422 control also has three single stage relay's that can be used as ventilation, heating or cooling controls.

DESCRIPTION

The VESCO422 control is a temperature-based control with two variable DC outputs and three relays. The VESCO422 comes with seven factory-configured operating programs which can be easily configured for your ideal situation.

The VESCO422 displays alert conditions such as high and low temperatures, power failure, and low line Voltage and can also connect to an alarm siren, alarm panel or auto-dialer. The VESCO422 is ideal for greenhouse and light-industrial buildings.



Environmental
Solutions, LLC.
vesenviro.com

8296 Commerce Pkwy,
Chippewa Falls, WI 54729 USA
Toll Free Tel.: (888) 622-2999
Tel.: (715) 720-0800
info@vesenviro.com